



SOUTH AFRICA

Data Sheet Grout 5kg

Stick a Tile – Tile Grout is a cement-based grout specially formulated for interior and exterior wall and floor applications.

Surface Preparation

1. Allow 24 hours for tile adhesive to dry before grouting with stick a tile grout. (For sealed or non-porous surfaces allow 48 hours).
2. Surface must be free of dust and all excess adhesive must be removed before grouting can start.
3. Seal unglazed tile with a sealer to prevent staining
4. Use a minimum joint width of 2mm on walls and 3mm on floors.
5. Do not butt-joint tiles

Mixing

1. Add gradually 5kg of Stick a Tile - Tile Grout to 1. 35 litres of cold clean water.
2. Mix to a creamy paste.
3. Allow mix to stand for 5 minutes.
4. Remix before use.
5. Do not mix more Stick a Tile - Tile Grout than can be used within +/- 1 hour.
6. In wet or permanently wet conditions, heavy traffic areas, or where some flexibility is required replace the water in the mix with Stick a Tile Bond. Note that Stick a Tile – Tile Grout mix with bond will dry a shade darker.
7. Do not add too much water or attempt to extend the working time by adding more water as this will cause the set grout to be weak with a tendency to crumble or powder. It may also cause surface discolouration and variation, especially with darker colours.

Application

1. Apply Stick a Tile -Tile Grout liberally to the surface and work into joints with a squeegee.
2. Completely fill the joints leaving no voids. Excess grout must be removed immediately.
3. Allow the grout to dry for 2 hours before cleaning with a damp (not wet) sponge
4. Do not allow any excess moisture to remain on the grout joints
5. The joints can be finished off by pointing along the joint lines
6. Allow 24 hours before polishing the joint lines with a dry clean cloth.

Guarantee

We guarantee that Stick a Tile products meet the product specification and will be free of any defect. Any guarantee with regard to the performance of Stick a Tile products will be subject to the professional and practical application of Stick a Tile products in accordance with our instructions and specifications. The guarantee would become void should the Stick a Tile product be contaminated or altered by the addition of cement, sand or substance other than recommended by us.

We have no influence over specific site conditions and therefore, if in doubt, the user should first carry out sufficient tests to ensure that the product is suitable. In special cases, obtain professional advice from the Stick a Tile technical department.

Note: It is required that we be informed within a reasonable time of suspected defect and afforded the opportunity to investigate the problem in detail.

Warning

Do not ingest. Keep away from children and pets. Do not empty in drains.

Precautions

Wear rubber gloves. In the event of contamination, rinse thoroughly with cold clean water and seek medical assistance if irritation or discomfort should occur.

Coverage

Use the following formulation to calculate the quantity of Stick a Tile - Tile Grout required per square metre of tiling :

$$\text{kg/m}^2 = \frac{A+B}{A \times B} \times C \times D \times 1.7$$

A = length of tile; B = width of tile; C = thickness of tile; D = average joint width

Product Properties

Final Setting Time:	24 hours at 20C
Pot Life:	90 minutes at 20C
Water Demand:	1.35 litres per 5kg
Application Temperature:	Do not apply below 5C or above 30C
Shelf life:	6 Months from production
Storage:	Store product in a dry and covered area at temperatures above 5C. Do not store directly on floor surface. Avoid large changes in temperature and humidity in storage environment.