



SOUTH AFRICA

PRODUCT DATA SHEET

STICK a TILE - BOND Latex Based Additive

Description

STICK a TILE BOND is a latex based additive for use together with **STICK a TILE** cement-based adhesive and **STICK a TILE "TILE GROUT"** to enhance flexibility, for increased bonding strength, for permanently wet areas or where extreme temperature changes are expected.

Preparation of Surface

Always refer to the instructions of the product to be used with **STICK a TILE BOND**. Ensure that the surfaces to be tiled are clean, free of loose material and correctly prepared.

Mixing Instructions

Replace the water ratio in the mix of **STICK a TILE** cement-based adhesive and **STICK a TILE "TILE GROUT"** with **STICK a TILE BOND** in the following areas: permanently wet areas, bathrooms, dairies, breweries, hospitals, abattoirs, cold rooms, swimming pools and walls or floors where extreme temperature changes are experienced. Refer to the product being used for correct mixing ratios.

NOTE: Cement and cement-based adhesives and grouts will dry a shade darker with the addition of **STICK a TILE BOND**. These products will also take approximately 12 hours longer to dry.

Packaging and Storage

STICK a TILE BOND is available in 1 lt, 5 lt and 25lt plastic containers. **STICK a TILE BOND** must be stored at a moderate temperature in an airtight container.

Coverage

Refer to the product been used with **STICK a TILE BOND** for the approximate coverage.

Precautions

Wear protective clothing and rubber gloves. In the event of contamination, rinse thoroughly with cold water. Seek medical attention if irritation or discomfort should occur.

Warning

Do not ingest. Keep away from children and pets. Do not empty into drains.

Guarantee

STICK a TILE BOND is guaranteed if used in accordance with our product application instructions. This guarantee falls away should any substance be added to **STICK a TILE BOND** other than those recommended by **STICK a TILE**.