



SOUTH AFRICA

PRODUCT DATA SHEET

STICK a TILE SUPER STICK Ready Mixed Paste Tile Adhesive

Description

STICK a TILE SUPER STICK Paste Tile Adhesive is a ready mixed, thin-bed tile adhesive for applications onto internal and external walls and floors. It can be used for fixing of ceramic tiles, timber or chipboard that is primed, plaster, concrete tiles and chipped and primed gypsum plaster.

Preparation of Surface

- All surfaces to be tiled must be firm.
- Remove all loose material, dirt, moisture, oil, organic growth, etc.
- Surfaces, which have been painted, must be chipped to expose 80% of the surface area.
- Gypsum-plastered surfaces should be treated as painted surface
- Bitumen or enamel paint must be totally stripped of these materials by scrapping or using the correct solvent-based remover and then chipped to expose 80% of the surface area.
- Very smooth surfaces must be acid washed and then cleaned with clean water. The area must be allowed to dry.

Mixing Instructions

STICK a TILE SUPER STICK is a ready mixed product and nothing must be added. Stir the product before use only.

How to Apply

- Apply **STICK a TILE SUPER STICK** with the correct notched tiling trowel to the surface. The minimum bedded thickness on walls is 3mm and floors 6mm.
- Bed tiles firmly into the wet adhesive ensuring 100% contact between tile and adhesive. Use a twisting action when bedding tiles.
- Do not butt joint tiles.
- Ensure that excess adhesive is removed from the joints and tiles before it dries.

Packaging and Storage

STICK a TILE SUPER STICK is packed in 2 kg and 5 kg plastic buckets. The product must be stored at room temperature, in its container with the lid tightly closed.

General Rules

- Do not soak tiles before laying only use dry tiles.
- All tiles must make 100% contact with the adhesive, as hollow areas will result in cracked tiles.
- Movement joints should be provided for every 3 meters, in both directions, and filled with a mastic sealer.
- Expansion joints in buildings must be extended through the tiles and adhesive bed and filled with a mastic sealer.
- Perimeter joints must be filled with a mastic sealer.

Grouting

- The minimum grouting joints on walls is 2mm and on floors is 5mm.
- The tiles must be left to dry for 24 hours before grouting can take place.

Precautions

Wear protective clothing and rubber gloves. In the event of contamination, rinse thoroughly with cold water. Seek medical assistance if irritation or discomfort should occur.

Warning

Do not ingest. Keep away from pets and children. Do not empty into drains.

Guarantee

We guarantee **STICK a TILE** products meet the product specification and will be free of any defect. Any guarantee with regard to the performance of **Stick a Tile** products will be subject to the professional and practical application of **Stick a Tile** products in accordance with our instructions and specifications. The guarantee shall be become null and void should the **Stick a Tile** product be contaminated or altered by the addition of sand, cement or any other substance other than recommended by us. NOTE: We are to be informed within a reasonable time of suspected defects and afforded the opportunity to investigate the problem in detail.